


SIZE	FILTER TYPE	CAPACITANCE (pF)		VOLTAGE		CURRENT RATING	CONTACT RESISTANCE	MINIMUM ATTENUATION (dB)							
		MIN	MAX	WVDC	DWV			5 MHz	10 MHz	20 MHz	50 MHz	100 MHz	200 MHz	500 MHz	1 GHz
50	C	400	600	100	250	5A	.010 Ohms			3	10	15	22	31	37



NOTES

- 1) SHELLS: STEEL, TIN PLATED.
- 2) CONTACTS: COPPER ALLOY, GOLD PLATED, .000010" TYP.
- 3) INSULATORS AND BACK COVER: PLASTIC, UL94-V0.
- 4) OPERATING TEMPERATURE: -55°C TO +125°C.
- 5) MARKING: PART NUMBER IS INK STAMPED ON REAR COVER.
- 6) EACH UNIT INCLUDES TWO #4-40 THUMBSCREWS (NOT SHOWN). EACH THUMBSCREW IS CAPTIVE WITHIN THE MOUNTING HOLES.

DATE	C.O.	REV																
10/26/06	--	A																

ALL DIMENSIONS ARE IN INCHES (mm)
GENERAL TOLERANCES UNLESS OTHERWISE SPECIFIED
DECIMAL: ± .025 [.64]
ANGLES: ± 1°
CAGE CODE 15717

**CORRY Micronics** One Plastics Rd. - Corry, PA 16407  
(814) 664-7728 FAX (814) 664-4582  
www.cormic.com

Dwg By: RPM Date: 10/26/06 Chk'd By: RPM  
Scale: 1X File: Sheet:

50 PIN, ADAPTER, 500 PF "C"  
DSC50-300-L00